Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-003-8275

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

2.277 inches

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.250 inches

## Shaft Length:

0.812 inches

## Mounting Bushing Length:

# 0.358 inches

**Body Length:** 

## 1.465 inches

**Overall Diameter:** 

# 0.875 inches

Shaft Style:

#### Round

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

2.00 inch-ounces

#### Maximum Running Torque:

2.00 inch-ounces

#### **Terminal Location:**

Longitudinally positioned on the circumference

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

1.000 kilohms single section

# **Rotary Actuator Travel In Angular Deg:**

3600.0

# Power Dissipation Rating Per Section In Watts:

1.5 free air single section

# Function Conformity Per Section:

Single section independent linearity



**Resistance Tolerance Per Section In Percent:** 

-3.0/+3.0 single section

## Actuator Travel Control Feature:

Continuous motion

**Function Characteristic Per Section:** 

Single section linear

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0