Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-004-7590

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# Reliability Indicator:

Not established

## **Overall Length:**

1.308 inches

## **Terminal Length:**

6.000 inches

**Overall Height:** 

## 0.315 inches

**Overall Width:** 

#### 0.190 inches

Mounting Hole Diameter:

## 0.093 inches

Shaft Diameter:

0.115 inches

## Shaft Length:

0.058 inches

# Body Length:

1.250 inches

#### Body Width:

0.190 inches

#### **Body Height:**

0.315 inches

#### Shaft Style:

Round, slotted

## Shaft Bearing Type:

Bearing

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

7920.0

## Maximum Starting Torque:

8.00 inch-ounces

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

## **Mounting Facility Quantity:**

- 2
- **Terminal Location:**

Rear end



# **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 100.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section **Test Data Document:** 81349-milr22097/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 wire lead Shelf Life: Unit Of Measure: **Demilitarization:** Fiig:

A002a0

N/a

---

No