

View Online at <https://aerobasegroup.com/nsn/5905-01-004-9399>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.828 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.625 inches

**Mounting Bushing Length:**

0.281 inches

**Body Length:**

1.094 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

117.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

295.0

**Maximum Starting Torque:**

27.00 inch-ounces

**Maximum Running Torque:**

6.00 inch-ounces

**Maximum Stop Torque:**

192.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.531 inches

**Switch Operating Position:**

End of rotation

**Switch Contact Arrangement:**

Single pole, double throw, three positions maintained

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Cubic Measure:**

0.185 cubic inches

**Electrical Resistance Per Section:**

5.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

330.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0/+6.9 -55 degrees celsius single section and +0.0/+3.8 -25 degrees celsius single section and +0.0/+1.9 0 degrees celsius single section and -2.5/+2.5 85 degrees celsius single section and +0.0/+5.6 120 degrees celsius single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Switch Current Type And Rating In Amps:**

3.000 ac/dc

**Standard Taper Curve Per Section:**

C single section

**Test Data Document:**

80063-sm-c-746958 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A002a0