NSN 5905-01-005-1489

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-005-1489 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.810 inches **Body Diameter:** 1.810 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.810 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.000 inches **Overall Diameter:** 2.164 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches

Shaft Runout: 0.0005 inches **Lateral Runout:** 0.003 inches

NSN 5905-01-005-1489

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately delicate
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Criticality Code Justification:
Feat
Function Characteristic Per Section:
7 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Item must comply with requirements of defense electronics supply center production standard no. L01814
Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-01-005-1489

Precision Wire Wound Variable Resistor - Page 3 of 3



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0