NSN 5905-01-005-4945

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-005-4945

Section Quantity:
1
Body Style:
Rectangular w/bushing/slot mounted
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.075 mils and 0.080 centimeters
Shaft Diameter:
Between 0.088 inches and 0.098 inches
Shaft Length:
Between 0.266 inches and 0.296 inches
Mounting Bushing Length:
Between 0.266 inches and 0.296 inches
Body Length:
Between 0.454 inches and 0.484 inches
Body Width:
Between 0.313 inches and 0.343 inches
Body Height:
Between 0.454 inches and 0.484 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 6480.0 and 10080.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Fragility Factor:
Moderately rugged
Lateral Distance Between Mounting Hole Centers:
Between 0.370 inches and 0.380 inches
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
UE:U

NSN 5905-01-005-4945

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Standard bushing and unthreaded hole
Features Provided:
Humidity proof
Cubic Measure:
0.072 cubic inches
Electrical Resistance Per Section:
50.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 6480.0 and 10080.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Sealed to permit cleaning in common solvents
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0