NSN 5905-01-006-0090

Section Quantity:

Cylindrical bushing mounted

Between 0.249 inches and 0.250 inches

Reliability Indicator:

Not established **Body Diameter:**1.000 inches **Shaft Diameter:**

Shaft Length:

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-006-0090

1.000 inches
Mounting Bushing Length:
0.500 inches
Body Length:
1.344 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Fragility Factor:
Moderately delicate
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section

NSN 5905-01-006-0090

Precision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:	
3.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
40.0 single section	
Terminal Type And Quantity:	
3 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	