

View Online at https://aerobasegroup.com/nsn/5905-01-006-7701

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

2.281 inches

### **Body Diameter:**

0.875 inches

## Shaft Diameter:

0.125 inches

### Shaft Length:

0.750 inches

## Mounting Bushing Length:

# 0.251 inches

**Body Length:** 

1.500 inches

## Overall Diameter:

1.069 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

## Maximum Starting Torque:

0.70 inch-ounces

## Maximum Running Torque:

0.60 inch-ounces

## Maximum Stop Torque:

48.00 inch-ounces

#### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.001 inches

## Lateral Runout:

0.001 inches

### **Pilot Diameter Runout:**

0.001 inches

## Shaft Radial Play:

0.002 inches

1.0

Unef

32.0

N/a

Unit Of Measure:



Mechanical Backlash In Deg Angular Rotation: Screw Thread Diameter: 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 turret **Specification Data:** 81349-mil-r-12934/31 government specification Shelf Life:



Demilitarization:

No

Fiig:

A002a0