## NSN 5905-01-007-1448

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-007-1448 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 6.415 inches **Terminal Length:** 6.000 inches **Overall Height:** 0.375 inches **Overall Width:** 0.203 inches **Mounting Hole Diameter:** 0.074 inches **Shaft Diameter:** 0.090 inches **Shaft Length:** 0.040 inches **Body Length:** 0.375 inches **Body Width:** 0.203 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces

**Mounting Facility Quantity:** 1 **Terminal Location:** Rear end **Mounting Method:** 

Unthreaded hole

**Electrical Resistance Per Section:** 

100.000 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

9000.0

## NSN 5905-01-007-1448

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

**Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** 

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0