NSN 5905-01-007-6253

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-007-6253 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.5000 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.031 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.380 inches **Body Length:** 0.725 inches **Mounting Lip Diameter:** 1.8750 inches **Mounting Lip Depth:** 0.0930 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Shaft End Play:** 0.005 inches **Shaft Runout:**

0.002 inches **Lateral Runout:**0.001 inches

NSN 5905-01-007-6253

A002a0

Precision Nonwire Wound Variable Resistor - Page 2 of 2



| Pilot Diameter Runout: |
|---|
| 0.001 inches |
| Shaft Radial Play: |
| 0.005 inches |
| Mechanical Backlash In Deg Angular Rotation: |
| 0.1 |
| Undercut Length: |
| 0.921 inches |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Clamp ring |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Function Conformity Tolerance Per Section: |
| -0.05/+0.05 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Special Features: |
| Shaft screwdriver slotted 0.050 in. Deep by 0.031 in. W, 1 no. 0 (0.060 in. Dia) -80 thd hole 0.250 in. Min deeep centered in shaft |
| Terminal Type And Quantity: |
| 3 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |