Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-007-6262

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.308 inches

#### **Terminal Length:**

0.500 inches

**Overall Height:** 

#### 0.815 inches

**Overall Width:** 

#### 0.190 inches

Mounting Hole Diameter:

## 0.093 inches

Shaft Diameter:

0.115 inches

## Shaft Length:

0.058 inches

# Body Length:

1.250 inches

#### Body Width:

0.190 inches

#### Body Height:

0.315 inches

#### Shaft Style:

Round, slotted

Actuator Type:

Single shaft

## Center To Center Distance Between Terminals:

0.700 inches

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

### **Terminal Location:**

Lower adjacent side single row

### **Mounting Method:**

Unthreaded hole and terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

# NSN 5905-01-007-6262

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## **Electrical Resistance Per Section:**

50.0 kilohms single section

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

# Test Data Document:

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 pin

Specification Data:

81349-mil-r-22097/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0