## NSN 5905-01-007-6276

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-007-6276 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0600 inches **Overall Length:** 1.805 inches **Undercut Diameter:** 2.00000 inches **Undercut Width:** 0.0600 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 0.985 inches **Overall Diameter:** 2.312 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0600 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Terminal Location:** Radially positioned over more than half the circumference **Mounting Method:** Clamp ring

**Electrical Resistance Per Section:** 

2.0 kilohms single section

## NSN 5905-01-007-6276

Precision Nonwire Wound Variable Resistor - Page 2 of 2



## **Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:** 100.0 single section **Function Conformity Tolerance Per Section:** -1.00/+1.00 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A002a0