NSN 5905-01-008-5054

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-008-5054

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Rectangular w/mounting holes |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.188 inches |
| Mounting Hole Diameter: |
| 0.073 inches |
| Shaft Diameter: |
| 0.060 inches |
| Shaft Length: |
| 0.040 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.255 inches |
| Body Height: |
| 0.500 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 16200.0 |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Lateral Distance Between Mounting Hole Centers: |
| 0.520 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Left adjacent side two rows |
| Mounting Method: |
| Unthreaded hole |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Electrical Resistance Per Section: |
| 300.0 ohms single section |
| Rotary Actuator Travel In Angular Deg: |

16200.0

NSN 5905-01-008-5054

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Center To Center Distance Between Center Terminal And Outside Terminal: |
|--|
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 50.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |