

View Online at <https://aerobasegroup.com/nsn/5905-01-008-8429>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Overall Length:**

0.482 inches

**Terminal Length:**

0.300 inches

**Overall Height:**

0.375 inches

**Overall Width:**

0.455 inches

**Shaft Diameter:**

Between 0.050 inches and 0.750 inches

**Shaft Length:**

0.080 inches

**Body Length:**

0.420 inches

**Body Width:**

Between 0.140 inches and 0.200 inches

**Body Height:**

Between 0.360 inches and 0.390 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 5400.0 and 10800.0

**Maximum Running Torque:**

5.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.100 inches

**Terminal Location:**

Rear end

**Mounting Method:**

Terminal

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 5400.0 and 10800.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.200 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.75 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Test Data Document:**

81349-mil-prf-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 pin

**Specification Data:**

81349-mil-prf-39015/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0

**Mil-std (military Standard):**

Mil-prf-39015 spec.