NSN 5905-01-008-9264

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-008-9264

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.308 inches
Overall Height:
0.470 inches
Overall Width:
0.190 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.115 inches
Shaft Length:
0.058 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.320 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

NSN 5905-01-008-9264

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Criticality Code Justification:
Feat
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Item must comply with requirements of defense electronics @supply center production standard no. L01836
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0