Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-008-9272

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

### **Overall Length:**

0.375 inches

#### Terminal Length:

0.188 inches

#### **Overall Height:**

0.375 inches

#### **Overall Width:**

0.360 inches

### Body Length:

### 0.375 inches

# Body Width:

0.188 inches

# Body Height:

0.375 inches

### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

240.0

### Maximum Starting Torque:

5.00 inch-ounces

### Center To Center Distance Between Terminals:

0.200 inches

### **Terminal Location:**

Rear end

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

5.000 kilohms single section

### Rotary Actuator Travel In Angular Deg:

360.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section



**Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Distance between terminals on width side 0.200in. **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0