

View Online at <https://aerobasegroup.com/nsn/5905-01-009-0002>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-50.0/+50.0

**Electrical Resistance:**

467.000 ohms

**Resistance Tolerance In Percent:**

-0.100/+0.100

**Ambient Temperature In Deg Celsius At Full Rated Power:**

125.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

175.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0/+175.0

**Inclosure Method:**

Encapsulated

**Terminal Type:**

Wire lead

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Body Diameter:**

0.109 inches

**Body Length:**

0.250 inches

**Power Dissipation Rating In Watts:**

0.100 free air

**End Application:**

Nimitz class cvn; tarawa class lha; emory s. Land class as; 2m/ate microminature automatic test equipment; ticonderoga class cg (47); arleigh burke class ddg; oliver perry class ffg; tactical data system, an/uva- (v)

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Style Designator:**

Axial terminal each end

**Test Data Document:**

81349-milr55182/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A001a0