NSN 5905-01-009-2546

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-009-2546 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.6300 inches Pilot Length: 0.0620 inches **Overall Length:** 1.188 inches **Undercut Diameter:** 0.630 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.437 inches **Body Length:** 0.625 inches **Overall Diameter:** 0.875 inches **Mounting Lip Diameter:** 0.7500 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 340.0 **Maximum Starting Torque:** 0.05 inch-ounces

Maximum Running Torque:

0.02 inch-ounces

NSN 5905-01-009-2546

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.003 inches
Shaft Radial Play:
0.003 inches
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
Power Dissipation Rating Per Section In Watts: 7.0 free air single section
7.0 free air single section
7.0 free air single section Function Conformity Per Section:
7.0 free air single section Function Conformity Per Section: Single section independent linearity
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 turret
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 turret Shelf Life:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 turret Shelf Life: N/a
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 turret Shelf Life: N/a
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure:
7.0 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: