

View Online at <https://aerobasegroup.com/nsn/5905-01-009-3548>

Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:

-30.0/+30.0 first temp coefficient

Electrical Resistance:

1.000 kilohms each resistor

Resistance Tolerance In Percent:

-1.000/+1.000 each resistor

Heat Sink Material:

Aluminum alloy

Heat Sink Length:

6.000 inches

Heat Sink Width:

5.000 inches

Heat Sink Height:

2.000 inches

Heat Sink Thickness:

0.040 inches

Ambient Temperature In Deg Celsius At Full Rated Power:

25.0

Ambient Temperature In Deg Celsius At Zero Percent Rated Power:

275.0

Temperature Range Of Temperature Coefficient In Deg Celsius:

-55.0/+275.0 temp range of first temp coefficient

Inclosure Method:

Encased

Terminal Type:

Tab, solder lug

Reactance Characteristic:

Noninductive

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Terminal Length:

0.266 inches

Body Length:

0.600 inches

Body Width:

0.334 inches

Body Height:

0.320 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.444 inches

Power Dissipation Rating In Watts:

3.000 free air

Terminal Width:

0.085 inches

Mounting Hole Size:

0.093 inches

Style Designator:

Axial terminal (s)

Test Data Document:

81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-39009/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.