## NSN 5905-01-009-3548

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-009-3548
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0/+30.0 first temp coefficient
Electrical Resistance:
1.000 kilohms each resistor
Resistance Tolerance In Percent:
-1.000/+1.000 each resistor
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
6.000 inches
Heat Sink Width:
5.000 inches
Heat Sink Height:
2.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0 temp range of first temp coefficient
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reactance Characteristic:
Noninductive
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
0.266 inches
Body Length:
0.600 inches
Body Width:
0.334 inches
Body Height:
0.320 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.444 inches

NSN 5905-01-009-3548 Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Power Dissipation Rating In Watts:
3.000 free air
Terminal Width:
0.085 inches
Mounting Hole Size:
0.093 inches
Style Designator:
Axial terminal (s)
Test Data Document:
31349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-prf-39009/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4001a0
Mil-std (military Standard):
Mil-prf-39009 spec.