NSN 5905-01-009-5549

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-009-5549

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.060 inches
Terminal Length:
0.250 inches
Overall Height:
0.560 inches
Overall Width:
0.280 inches
Mounting Hole Diameter:
0.086 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.060 inches
Body Length:
1.000 inches
Body Width:
0.280 inches
Body Height:
0.360 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.500 inches
Lateral Distance Between Mounting Hole Centers:
0.830 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole and terminal
Center To Center Distance Retween Terminal Power

0.200 inches

NSN 5905-01-009-5549

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:

10.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0