Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-009-7568

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9688 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.968 inches

Undercut Width:

0.0570 inches

Body Diameter:

1.062 inches

Shaft Diameter:

Shart Diameter.

0.1248 inches

Shaft Length:

0.500 inches

Body Length:

0.815 inches

Mounting Lip Diameter:

1.0620 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.25 inch-ounces

Maximum Running Torque:

0.25 inch-ounces

Shaft End Play:

0.003 inches

Shaft Runout:

0.002 inches

NSN 5905-01-009-7568

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.003 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
340.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
1.25 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0