

View Online at <https://aerobasegroup.com/nsn/5905-01-010-1044>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.2495 inches and 0.2500 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.750 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

Shaft End Play:

0.010 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.004 inches

Pilot Diameter Runout:

0.004 inches

Shaft Radial Play:

0.002 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

Between 3600.0 and 3610.0

Function Conformity Tolerance Per Section:

-0.20/+0.20 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0