Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-010-1806

# Section Quantity:

1

# Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

# **Pilot Diameter:**

Between 2.8740 inches and 2.8750 inches

#### **Pilot Length:**

0.0630 inches

#### **Overall Length:**

3.251 inches

#### **Undercut Diameter:**

Between 2.87400 inches and 2.87500 inches

#### Undercut Width:

# 0.0800 inches

**Body Diameter:** 

3.000 inches

### Shaft Diameter:

Between 0.2495 inches and 0.250 inches

#### Shaft Length:

0.750 inches

#### Body Length:

2.437 inches

#### **Overall Diameter:**

3.250 inches

#### Mounting Lip Diameter:

3.0000 inches

# Mounting Lip Depth:

0.0930 inches

#### Shaft Style:

Round

#### Shaft Bearing Type:

Ball

#### **Contact Arm Electrical Off Position:**

Fully cw

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

355.0

# Maximum Starting Torque:

2.25 inch-ounces

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft End Play: 0.005 inches Shaft Runout: 0.001 inches Lateral Runout: 0.003 inches **Pilot Diameter Runout:** 0.001 inches Shaft Radial Play: 0.001 inches Mechanical Backlash In Deg Angular Rotation: 0.01 **Terminal Location:** Rear end **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 4.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.025/+0.025 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 10.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 4 turret Shelf Life:

N/a

# NSN 5905-01-010-1806

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0