NSN 5905-01-010-1806

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-010-1806 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 2.8740 inches and 2.8750 inches Pilot Length: 0.0630 inches **Overall Length:** 3.251 inches **Undercut Diameter:** Between 2.87400 inches and 2.87500 inches **Undercut Width:** 0.0800 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** Between 0.2495 inches and 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 2.437 inches **Overall Diameter:** 3.250 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Contact Arm Electrical Off Position:** Fully cw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 355.0

Maximum Starting Torque:

2.25 inch-ounces

NSN 5905-01-010-1806

Precision Nonwire Wound Variable Resistor - Page 2 of 3



N/a

NSN 5905-01-010-1806

Precision Nonwire Wound Variable Resistor - Page 3 of 3



		• •					
ш	ın	ıtı	r 1t	NЛ	മാ	CII	re:

--

Demilitarization:

No

Fiig:

A002a0