NSN 5905-01-010-7532

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-010-7532

| Section Quantity: |
|--|
| 1 |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 0.500 inches |
| Shaft Diameter: |
| 0.125 inches |
| Shaft Length: |
| 0.944 inches |
| Mounting Bushing Length: |
| 0.250 inches |
| Body Length: |
| 0.375 inches |
| Shaft Style: |
| Round |
| Actuator Type: |
| Single shaft |
| |
| Effective Electrical Rotation In Deg Angular Rotation: |
| Effective Electrical Rotation In Deg Angular Rotation: 350.0 |
| |
| 350.0 |
| 350.0 Nonturn Device Location: |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 |
| 350.0 Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: |
| Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference |
| Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: |
| Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing |
| Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: |
| Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 550.0 ohms single section |
| Nonturn Device Location: At 6 oclock and at 12 oclock Screw Thread Diameter: 0.250 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 Terminal Location: Radially positioned over less than half the circumference Mounting Method: Standard bushing Electrical Resistance Per Section: 550.0 ohms single section Rotary Actuator Travel In Angular Deg: |

Stops

Actuator Travel Control Feature:

NSN 5905-01-010-7532

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Standard Taper Curve Per Section |
|----------------------------------|
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A002a0