NSN 5905-01-010-7537

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-010-7537

Section Quantity:	
1	
Body Style:	
Cylindrical bushing mounted	
Reliability Indicator:	
Not established	
Overall Length:	
1.625 inches	
Body Diameter:	
0.969 inches	
Shaft Diameter:	
0.250 inches	
Shaft Length:	
0.875 inches	
Mounting Bushing Length:	
0.375 inches	
Body Length:	
0.750 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Fragility Factor:	
Moderately rugged	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Standard bushing	
Electrical Resistance Per Section:	
1.0 megohms single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
105.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
00.0/.00.0 = in the continu	

-30.0/+30.0 single section

NSN 5905-01-010-7537

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature in Deg Ceisius Per Section At Full Rated Powel
40.0 single section
Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0