Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-010-9906

Section	Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

**Overall Length:** 

0.453 inches

Terminal Length:

0.187 inches

Body Diameter:

0.800 inches

Body Length:

0.250 inches

**Overall Diameter:** 

# 0.800 inches

Actuator Type:

Flush drive with slot-hole

### **Center To Center Distance Between Terminals:**

0.200 inches

**Terminal Location:** 

Rear end

#### **Mounting Method:**

Terminal

### Center To Center Distance Between Terminal Rows:

0.100 inches

**Electrical Resistance Per Section:** 

5.0 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

### Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

### Standard Taper Curve Per Section:

A single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0