## NSN 5905-01-011-0617

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-011-0617

| On attent Occantition   |
|---|
| Section Quantity:   |
| 1<br>Party Styles   |
| Body Style:   |
| Rectangular w/mounting holes/slots  |
| Reliability Indicator:  |
| Not established   |
| Overall Length:   |
| 0.452 inches  |
| Terminal Length:  |
| 0.172 inches  |
| Overall Height:   |
| 0.332 inches  |
| Overall Width:  |
| 0.160 inches  |
| Body Length:  |
| 0.417 inches  |
| Body Width:   |
| 0.160 inches  |
| Body Height:  |
| 0.375 inches  |
| Actuator Type:  |
| Integral knob   |
| Center To Center Distance Between Terminals:                                |
| 0.200 inches  |
| Terminal Location:  |
| Rear end  |
| Mounting Method:  |
| Terminal  |
| Electrical Resistance Per Section:  |
| 500.000 ohms single section   |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.100 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 175.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -50.0/+50.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 1.0 free air single section   |
| Resistance Tolerance Per Section In Percent:                                |
| -5.0/+5.0 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 steple continu   |

70.0 single section

## NSN 5905-01-011-0617

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Standard Taper Curve Per Section |
|----------------------------------|
| A single section                 |
| Terminal Type And Quantity:      |
| 3 pin                            |
| Shelf Life:                      |
| N/a                              |
| Unit Of Measure:                 |
|                                  |
| Demilitarization:                |
| No                               |
|                                  |

Fiig: A002a0