NSN 5905-01-012-3765

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-012-3765

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.459 inches
Terminal Length:
0.188 inches
Body Diameter:
Between 0.234 inches and 0.266 inches
Body Length:
0.281 inches
Overall Diameter:
Between 0.234 inches and 0.266 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
215.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
2.5 kilohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:

Stops

NSN 5905-01-012-3765

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: