Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-012-8905

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

### **Terminal Length:**

0.150 inches

#### Shaft Diameter:

0.095 inches

#### Shaft Length:

0.060 inches

### Body Length:

0.750 inches

#### Body Width:

0.190 inches

# Body Height:

0.250 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

7200.0

### **Center To Center Distance Between Terminals:**

0.500 inches

### **Terminal Location:**

Lower adjacent side two rows

### **Mounting Method:**

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

25.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

7200.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# NSN 5905-01-012-8905 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

### Fiig:

A002a0