NSN 5905-01-013-8269

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-013-8269 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.281 inches **Body Width:** 0.625 inches **Body Height:** 0.750 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 250.0 **Nonturn Device Location:** At 2 oclock **Nonturn Device Radius:** 0.312 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Electrical Resistance Per Section:** 250.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 250.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:**

A single section **Terminal Type And Quantity:** 3 tab, solder lug

NSN 5905-01-013-8269

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0