Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-013-8270

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.188 inches

#### **Overall Height:**

0.876 inches

#### **Overall Width:**

0.625 inches

#### Body Length:

0.188 inches

#### Body Width:

0.625 inches

# Body Height:

0.688 inches

#### 0.000 mones

Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

270.0

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

5.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

270.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### **Actuator Travel Control Feature:**

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0