## NSN 5905-01-014-2904

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-014-2904 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.937 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.000 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.0005 inches **Lateral Runout:** 0.003 inches **Pilot Diameter Runout:** 0.002 inches **Shaft Radial Play:** 0.003 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** 

Screw Thready Qty Per Inch (tpi): 32.0

NSN 5905-01-014-2904 Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-0.0/+130.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
19315-2132071 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0