## NSN 5905-01-014-6139

**Section Quantity:** 

Cylindrical bushing mounted

**Body Style:** 

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-014-6139

Reliability Indicator:
Not established
Overall Length:
2.218 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.312 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.453 inches
Overall Diameter:
0.500 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Maximum Stop Torque:
Maximum Stop Torque: 40.00 inch-ounces
40.00 inch-ounces
40.00 inch-ounces  Screw Thread Diameter:
40.00 inch-ounces  Screw Thread Diameter:  0.250 inches
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator:
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location:
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method:
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing
40.00 inch-ounces  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section:
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section: 5.000 megohms single section
40.00 inch-ounces  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Rear end  Mounting Method: Standard bushing  Electrical Resistance Per Section: 5.000 megohms single section  Function Conformity Tolerance Per Section:

## NSN 5905-01-014-6139

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.375 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Special Features:** Mtg bushing insulated from resistance unit by a 1.100 in. Lg insulator **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**