Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-014-7734

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

0.938 inches

### Shaft Diameter:

0.250 inches

### Shaft Length:

0.219 inches

## Mounting Bushing Length:

0.453 inches

### Body Length:

## 0.500 inches

Shaft Style:

### Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

360.0

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

### **Electrical Resistance Per Section:**

1.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

360.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# NSN 5905-01-014-7734

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0