Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-014-7735

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Overall Length:

0.672 inches

Body Diameter:

0.937 inches

Body Length:

0.453 inches

Overall Diameter:

1.375 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Tab

Electrical Resistance Per Section:

5.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-30.0/+30.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0