## NSN 5905-01-015-1643

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-015-1643 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** 2.689 inches **Overall Height:** 1.000 inches **Overall Width:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.938 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.563 inches **Body Width:** 0.875 inches **Body Height:** 1.000 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Rear end

Mounting Method: Standard bushing

## NSN 5905-01-015-1643

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0