NSN 5905-01-015-3928

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-015-3928

Electrical Resistance: 22.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tompurature Coefficient Of Projetones In Dam Bor Dog Coloius
Electrical Resistance: 22.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
22.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
-5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	-55.0 to 150.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type:
Not established Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Wire lead
Terminal Length: 1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Reliability Indicator:
1.500 inches Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Not established
Body Diameter: Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Length:
Between 0.305 inches and 0.325 inches Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	1.500 inches
Body Length: Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Diameter:
Between 0.656 inches and 0.718 inches Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.305 inches and 0.325 inches
Power Dissipation Rating In Watts: 2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Length:
2.000 free air Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.656 inches and 0.718 inches
Unpackaged Unit Weight: 1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
1.000 grams Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	2.000 free air
Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	Unpackaged Unit Weight:
Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization:	1.000 grams
Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
N/a Unit Of Measure: Demilitarization:	Axial terminal each end
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	Fiig:
A001a0	A001a0