Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-015-5656

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

1.500 inches

Terminal Length:

0.250 inches

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Body Length:

0.625 inches

Overall Diameter:

1.406 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Mounting Method:

Standard bushing and unthreaded hole

Electrical Resistance Per Section:

50.000 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.25 free air single section

NSN 5905-01-015-5656

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Function Conformity Per Section: Single section independent linearity **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0