NSN 5905-01-015-6330

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-015-6330 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted First Flat Length: 0.188 inches Flat Height: 0.093 inches **Body Diameter:** 1.047 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.063 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.250 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.000 ohms single section **Power Dissipation Rating Per Section In Watts:**

6.25 free air single section

NSN 5905-01-015-6330

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0