

View Online at <https://aerobasegroup.com/nsn/5905-01-016-0026>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

3.427 inches

Body Diameter:

0.781 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.444 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.140 inches

Overall Diameter:

0.967 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Nonturn Device Radius:

0.437 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Undercut Length:

0.444 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

20.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

50.0 ohms all sections

Rotary Actuator Travel In Angular Deg:

260.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Switch Current Type And Rating In Amps:

2.000 dc

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0