Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-016-0027

Section	Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

**Overall Length:** 

- 0.425 inches
- Terminal Length:

0.200 inches

Body Diameter:

0.450 inches

Body Length:

0.235 inches

**Overall Diameter:** 

0.450 inches

#### Actuator Type:

Flush drive with slot-hole

**Center To Center Distance Between Terminals:** 

0.100 inches

**Terminal Location:** 

Rear end

#### **Mounting Method:**

Terminal

### Center To Center Distance Between Terminal Rows:

0.200 inches

**Electrical Resistance Per Section:** 

2.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

310.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

## Actuator Travel Control Feature:

Continuous motion



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0