Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-016-0033 Section Quantity: 1 **Body Style:** Rectangular w/bushing/slot mounted **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.075 mils and 0.080 centimeters Shaft Diameter: Between 0.088 inches and 0.098 inches Shaft Length: Between 0.075 inches and 0.085 inches **Mounting Bushing Length:** Between 0.266 inches and 0.296 inches **Body Length:** Between 0.454 inches and 0.484 inches **Body Width:** Between 0.313 inches and 0.343 inches **Body Height:** Between 0.454 inches and 0.484 inches Shaft Style: Round, slotted Shaft Bearing Type: Sleeve Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6480.0 and 10080.0 **Maximum Starting Torque:** 5.00 inch-ounces Maximum Running Torque: 5.00 inch-ounces **Fragility Factor:** Moderately rugged Lateral Distance Between Mounting Hole Centers: Between 0.370 inches and 0.380 inches Screw Thread Diameter: 0.190 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Facility Quantity: 2 **Terminal Location:** Rear end **Mounting Method:** Standard bushing and unthreaded hole **Features Provided:** Humidity proof **Cubic Measure:** 0.047 cubic inches **Electrical Resistance Per Section:** 500.0 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** Between 6480.0 and 10080.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops and clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Sealed to permit cleaning in common solvents **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A002a0