NSN 5905-01-016-1088

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-016-1088 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Mounting Slot Width:** 0.093 inches **Shaft Diameter:** 0.025 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.187 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method: Electrical Resistance Per Section:** 200.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 7920.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-01-016-1088

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
10001-2995096 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Ferminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization: