NSN 5905-01-016-2382

Section Quantity:

150.0 single section

Body Style:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-016-2382

Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
0.300 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.375 inches
Body Width:
0.170 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 5400.0 and 10800.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Right adjacent side two rows
Mounting Method:
Terminal
Terminal Center To Center Distance Between Terminal Rows:
Center To Center Distance Between Terminal Rows:
Center To Center Distance Between Terminal Rows: 0.100 inches
Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section:
Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 2.0 kilohms single section
Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg:
Center To Center Distance Between Terminal Rows: 0.100 inches Electrical Resistance Per Section: 2.0 kilohms single section Rotary Actuator Travel In Angular Deg: Between 5400.0 and 10800.0

NSN 5905-01-016-2382

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
250.0/+250.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
35.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
31349-mil-r-39035/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No