NSN 5905-01-016-8568

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-016-8568

| Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius: -100.0/+100.0 Electrical Resistance: 237.000 ohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: 0.150 inches |
|---|
| Electrical Resistance: 237.000 ohms Resistance Tolerance In Percent: -1,000/+1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1,250 inches Body Diameter: 0.066 inches Body Length: |
| 237.000 ohms Resistance Tolerance In Percent: -1,000/+1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Reliability Failure Rate Level In Percent: 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| 0.010 Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Terminal Length: 1.250 inches Body Diameter: 0.066 inches Body Length: |
| 1.250 inches Body Diameter: 0.066 inches Body Length: |
| Body Diameter: 0.066 inches Body Length: |
| 0.066 inches Body Length: |
| Body Length: |
| |
| U. 150 Inches |
| Device Discinction Deting in Wetter |
| Power Dissipation Rating In Watts: |
| 0.125 free air |
| Unpackaged Unit Weight: |
| 0.300 grams |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-39017/5 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarization: |

No

NSN 5905-01-016-8568

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0