NSN 5905-01-017-6500

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-017-6500 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.535 inches **Overall Height:** 0.500 inches **Overall Width:** 0.187 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.060 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.187 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

Electrical Resistance Per Section:

50.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

NSN 5905-01-017-6500

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No