NSN 5905-01-017-7234

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-017-7234 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** 0.187 inches **Mounting Hole Diameter:** 0.073 mils and 0.083 centimeters **Shaft Diameter:** Between 0.058 inches and 0.098 inches **Shaft Length:** 0.045 inches **Body Length:** Between 0.490 inches and 0.510 inches **Body Width:** 0.230 inches **Body Height:** Between 0.490 inches and 0.510 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 8280.0 and 13680.0 **Maximum Starting Torque:** 10.00 inch-ounces **Maximum Running Torque:** 10.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Fragility Factor:** Moderately rugged **Lateral Distance Between Mounting Hole Centers:** Between 0.513 inches and 0.526 inches **Mounting Facility Quantity:**

2

Terminal Location:

Right adjacent side two rows

NSN 5905-01-017-7234

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
Between 0.095 inches and 0.105 inches
Features Provided:
Humidity proof
Cubic Measure:
0.052 cubic inches
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 8280.0 and 13680.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.095 mils and 0.105 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0