## NSN 5905-01-018-4272

Film Fixed Resistor - Page 1 of 2

**Fiig:** A001a0



View Online at https://aerobasegroup.com/nsn/5905-01-018-4272

Tompuvature Coefficient Of Resistance In Dam Der Der Celaius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
17.800 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+175.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.500 inches
Body Diameter:
0.125 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-55182/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5905-01-018-4272

Film Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-r-55182 spec.