Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-018-5555

## Section Quantity:

1

Body Style:

Rectangular bushing mounted

# Reliability Indicator:

Not established

## Shaft Diameter:

0.250 inches

### Shaft Length:

0.500 inches

### Mounting Bushing Length:

0.375 inches

Body Length:

0.594 inches

### Body Width:

0.625 inches

### **Body Height:**

0.625 inches

Shaft Style:

Round

### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Rear-bottom

## **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

2.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

300.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

#### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0